

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
13 January 2005 (13.01.2005)


PCT

(10) International Publication Number  
**WO 2005/003014 A3**

- (51) International Patent Classification<sup>7</sup>: **B60S 9/02**
- (21) International Application Number:  
PCT/US2004/020501
- (22) International Filing Date: 24 June 2004 (24.06.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
60/482,464 24 June 2003 (24.06.2003) US
- (71) Applicant: **RV SAFETY PRODUCTS, LLC** [US/US];  
10920 West Alameda Avenue, Suite 200, Lakewood, CO  
80226 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **RINCOE, Richard,  
G.** [US/US]; 17800 W. Colfax Avenue, C-7, Golden, CO  
80401 (US).
- (74) Agents: **MARTIN, Timothy, J.** et al.; Timothy J. Martin,  
P.C., 9250 W. 5th Avenue, Suite 200, Lakewood, CO 80226  
(US).
- (81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.
- (84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,

[Continued on next page]

(54) Title: **FORCE APPLYING APPARATUS AND METHOD**



(57) Abstract: A force applying apparatus includes a housing that supports a drive motor. A first extendable member is telescopically received in the housing and moves between a retracted position within the housing and an extended position axially of the housing. A second extendable member is telescopically received in the first extendable member and moves between a contracted position within the first extendable member and an expanded position axially of the first extendable member. The motor drives a ring gear that advances the first extendable member, and a ball nut is mounted in the end of the first extendable member to advance the second extendable member. A spline helps retain the first and second extendable members against rotation but a detent assembly selectively releases the first extendable member for rotation. The apparatus may be used to lift and level a recreational vehicle. A method implemented by this structure is also claimed.



FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,  
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG).

(88) Date of publication of the international search report:  
9 June 2005

**Published:**

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*